

## 5,08 mm SOCKET CABLE CONNECTOR MALE



Production Code : 510 SKBK



### TECHNICAL DATA

#### DIMENSIONS

|                   |          |
|-------------------|----------|
| Width             | 50,68 mm |
| Height            | 15,33 mm |
| Depth             | 22,00 mm |
| Pin range         | 5,08 mm  |
| Pin thickness     | 1x1 mm   |
| Pin hole diameter | 1,55 mm  |

### TECHNICAL DATA

|                     |                            |
|---------------------|----------------------------|
| Current             | 16 A                       |
| Voltage             | 250 V                      |
| Cable cross section | 0,25 – 2,5 mm <sup>2</sup> |
| Cable stripping     | 7 mm                       |
| Screw size          | M3                         |
| Nominal torque      | 0,25 Nm                    |
| Flammability rating | V0                         |
| Coating of metals   | μ3+AG                      |

### GENERAL ORDERING DATA

|                   |  |
|-------------------|--|
| Type              | 5,08 mm Socket Cable<br>Connector Male Pin 10        |
| Qty               | 50 pcs   |
| Order no          | 10.610 - 11.610 - 12.610<br>13.610 - 14.610 - 15.610 |
| Package weight    | 0,78 kg  |
| Packaging         | Box  |
| Min. Order Qty    | 50 pcs   |
| Country of origin | TURKEY   |

\* Stock color is blue.

### CERTIFICATES


| CERTIFICATE           | ISSUED BY     |
|-----------------------|---------------|
| TS 10487 EN 60998-2-1 | TSE           |
| CE                    | SZUTEST CO.   |
| RoHS                  | İNTERTEK A.Ş. |
| EAC                   | SERCONS       |



**MEGARADAR®**

Elektrik Elektronik İnşaat San. Tic. A.Ş.

## DRAWINGS



## COMBINE PRODUCTS

**5,08 mm SBDK-D (10.210)**



**5,08 mm Cable Connector Rail Distance (60.460)**

